


CLASSE H3 BORDO PONTE - BARRIERA 3 ONDE PER MANUFATTO W5

Class H3 Bridge side - 3-waves guardrail for bridge W5
Dreiwellen-Leitplanke auf Bauwerk, Aufhaltestufe H3, Wirkungsbereich W5
Classe H3 Bord de pont - Glissière 3 ondes simple pour pont W5
Clase H3 Borde de puente - Barrera de triple onda simple para puente W5




CARATTERISTICHE Characteristics, Eigenschaften, Caractéristiques, Características											
Altezza barriera Barrier height, Höhe Leitplanke, Hauteur glissière de sécurité, Altura barrera				1420 mm							
Profondità d'infissione tirafondi Anchor bolt embedment depth, Einschraubtiefe der Verankerungen, Profondeur de vissage des ancrages, Profundidad de anclaje varilla roscada				200 mm							
Ingombro trasversale Overall width, Gesamtbreite, Encombrement transversal, Anchura total				500 mm							
Interasse pali Post spacing, Steherabstand, Distance entre poteaux, Distancia entre postes				2250 mm							

RAPPORTI DI PROVA Crash test reports, Testberichte, Comptes rendus d'essais, Informes de ensayo											
Test n.	Facility	Test	Type	Barrier length m	Mass kg	Speed km/h	ASI	THIV max 33 km/h	D m	Vi m	W m
PROVA 880	AISICO	TB61	Laterale 20°	85,5	16.000	80	-	-	1,4	1,8	1,7=W5
PROVA 879	AISICO	TB11	Laterale 20°	85,5	900	100	1,3=B	25	0,4	-	0,5=W1

H3-W5

3-waves



COMPONENTI Components, Bauteile, Composants, Elementos			
Descrizione Description			Materiale Material
12	Morsetto per fune Cable clamp, Schraubklemme für Stahlseil, Serre-câble, Grapa para cable		Acc. zinc.
13		M16x35 mm	Classe 8.8
11		M16x170 mm	Classe 8.8
10		M16x50 mm	Classe 8.8
9	Bullone completo Bolt with nut and washer, Schraube komplett, Boulon complet, Tornillo completo con tuerca y arandela	M16x30 mm	Classe 8.8
8			
8	Tirafondo + dadi + 1 rondella Anchor bolt + nuts + 1 washer, Verbundklebeanschraube + Muttern + 1 Unterlegscheibe, Tire-fond + écrous + 1 rondelle, Varilla Roscada + tuercas + 1 arandela	M20x280 mm	Classe 8.8
7	Piastrina copriasola Slot covering plate, Lochabdeckplatte, Plaque de couverture fente, Placa cubre-ranura	100x40x4 mm	S 275 JR
6	Funne Wire rope, Seil, Câble, Cable	Ø12 L=6000 mm	Acc. zinc.
5	Collegamento trave "U" U-profile for beam connection, U-Profil für Geländerverbindung, Pièce de raccordement à "U", Perfil de conexión "U"	L=396 mm	S 355 JR
4	Distanziatore romboidale Rhomboidal spacer, Rhomboidisch. Abstandhalter, Entretoise en losange, Separador romboidal	Th=5 mm	S 235 JR
3	Trave superiore Upper T-beam, Geländerträger, Poutre supérieure, Viga superior	L=4490 Sv=450 mm	S 355 JR
2	Palo in tubo con piastra Rectangular tube post with base plate, Vierkantrohrsteher mit Grundplatte, Poteau tubulaire avec plaque, Poste de tubo con placa	120x80 H=1420 Th=5 mm	S 275 JR
1	Fascia 3 onde 3-waves beam, 3-wellige Leitschiene, Glissière 3 ondes, Banda triple onda	L=4816 (2250x2) Th=2,5 mm	S 235 JR