

Environmental Product Declaration

In accordance with
ISO 14025 and EN 15804:2012+A2:2019/AC:2021

TERMINAL FOR SAFETY BARRIERS

ACCORDING TO THE DEMANDS OF THE NORWEGIAN MARKET

Products not yet on the market

Marcegaglia Buildtech S.r.l.

Programme: The International EPD® System, www.environdec.com

Programme operator: EPD International AB
Licensee: **EPD International**
EPD registration number: **EPD-IES-0032281**

Type of EPD: **EPD of single product**

Version date: **2026-07-20**
Validity date: **2031-05-28**

An EPD may be updated or depublished if conditions change. To find the latest version of the EPD and to confirm its validity, see www.environdec.com

GENERAL INFORMATION 3
PROGRAMME INFORMATION 3
COMPANY INFORMATION 5
PRODUCTS INFORMATION 6
Terminal for safety barriers 6
LCA INFORMATION 7
DESCRIPTION OF MAIN ACTIVITIES 8
SYSTEM DIAGRAM 9
CONTENT INFORMATION 10
MODULES DECLARED 11
ENVIRONMENTAL INFORMATION 13
TERMINAL FOR SAFETY BARRIERS 14
ADDITIONAL ENVIRONMENTAL INFORMATION 16
VERSION HISTORY 17
ABBREVIATIONS 17
REFERENCES 17



GENERAL INFORMATION

PROGRAMME INFORMATION

Programme:	The International EPD® System
Address:	EPD International AB Box 210 60 SE-100 31 Stockholm Sweden
Website:	www.environdec.com
E-mail:	info@environdec.com

Standard EN 15804 serves as the Core Product Category Rules (PCR)

Product category rules (PCR):
Construction products, 2019:14, version 2.0.1., CPC 412

Complementary Product Category Rules (c-PCR) to PCR 2019:14:
Guardrails and bridge parapets, 2019:14, version 1.0.1, CPC 532.

PCR review was conducted by:
The Technical Committee of the International EPD System.
Review chair: Rob Rouwette (chair), Noa Meron (co-chair) – Contact through the secretariat
www.environdec.com/contact

Life Cycle Assessment (LCA)
LCA accountability: Made HSE S.r.l. – www.madehse.com
Adress: Via Bresciani, 16 – 46040 – Gazoldo degli Ippoliti (MN) – Italy
Mail: mattia.pelizzoni@madehse.com

Third-party verifier:
Independent third-party verification of the declaration and data, according to ISO 14025, via:
☒ EPD verification by accredited certification body

Third-party verification: *Bureau Veritas Italia S.p.A.* is an approved certification body accountable for the third-party verification
The certification body is accredited by: *Accredia*

Procedure for follow-up of data during EPD validity involves third party verifier:
☒ Yes ☐ No

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025.

Comparability between EPDs is only achievable if the following performance characteristics are equivalent: declared unit, containment level, level of working width, assumed service life, geographic region, and fulfilment of the same requirements of the applicable standard (EN 1317, NCHRP 350 or MASH).

COMPANY INFORMATION

Owner of the EPD:
Marcegaglia Buildtech S.r.l. - www.marcegagliabuildtech.it

Contact:
For more information on this product declaration and/or its configurations, the following references are available:
Technical Support
Mail: technicalsupportmb@marcegaglia.com Phone: +39 0143 7761 / +39 0230 7041

Company description:
Marcegaglia Buildtech S.r.l. is a company that manufactures a wide range of construction elements and products, as well as scaffolding for the civil and industrial construction sector thanks to the processing of semi-finished or finished products in steel: these elements include road barriers and guardrails.

Product/system certifications:
- Quality management system ISO 9001
- Environmental management system ISO 14001
- Health and safety management system ISO 45001
- Energy management system ISO 50001
- Social responsibility management system SA 8000
- Carbon Footprint Product Systematic Approach ISO 14067
- Road Traffic Safety (RTS) Management System ISO 39001
- UNI PdR 125 (Gender Integrity)
- Carbon Footprint Organization ISO 14064

Production site name and location:
Roveri street, 4 – 15068 Pozzolo Formigaro (AL).

PRODUCTS INFORMATION

Product name: Terminal for safety barriers according to the demands of the Norwegian market - Products not yet on the market

Product identification: Terminal for steel road safety barrier and steel guardrails

Product description:

Starting from the semi-finished steel products of guaranteed quality, subsequently hot dip galvanized, safety barriers and guardrails are created, certified by experimental tests, and developed in compliance with the specific regulations of the reference markets.

The Marcegaglia Buildtech range of safety barriers and steel guardrails is entirely manufactured at the Pozzolo Formigaro plant (Alessandria), which is equipped with the latest production technologies to ensure top product performance. Detailed product catalogs, including comprehensive technical specifications, are available for consultation on the company website.

The EPD presented is based on the assumption and future development of barriers manufactured using low-carbon steel coils as the main raw material. Since these products are not yet commercially available on the market at the time of the study, the declaration is classified as an “EPD not yet on the market.”

TECHNICAL DATA OF THE PRODUCT

The parameters listed below are specified for each element contained in this study:

- Containment level (eg: T1, N1, H1 etc.);
- Impact severity level (eg: A, B, C);
- Operating width level (eg: W1, W2 etc.);
- Vehicle intrusion class (eg: Vi2, Vi4, Vi8 etc.);
- Normalized dynamic deflection (expressed in meters).

Terminal for safety barriers

Barrier	Containment level	Impact severity level	Working width	Vehicle intrusion	Dynamic deflection	Weight [kg]	Lenght [m]
P4 Terminal Element	P4	B	W4	X1 e Y2	P4	633.9	12.21

UN CPC code: UN CPC 532 “Civil engineering works”

Geographical scope: Global

LCA INFORMATION

The scope of this EPD is to assess potential environmental impact values for 1 ton of Terminal for safety barriers, based on the Life Cycle Assessment methodology and make them explicit. A description with details on declared unit, system boundaries, key assumptions and flow chart of the lifecycle stages included, is reported in the following paragraphs.

Declared unit:
The declared unit of the system considered is the linear meter of the safety barrier.

Reference service life – RSL:
The expected durability, as a function of the atmospheric environment in which the road safety barrier is installed, is consistent with the provisions of UNI EN ISO 1461:2022, which specifies the requirements for hot-dip galvanized coatings, including minimum coating thicknesses that directly influence corrosion resistance and service life.
However, the actual service life may vary in highly corrosive environments and/or under specific exposure conditions, such as severe marine atmospheres or in the presence of mechanical damage due to abrasive agents (e.g. wind-blown sand), which can locally accelerate coating degradation.

Time representativeness:
The data used is representative of the year 2025.

Database e software:
Ecoinvent database v.3.11, April 2025 / Software used SimaPro rel. 10.3.0.1

Description of system boundaries:
The study is ”Cradle to gate with options, modules C1–C4, module D and with optional modules (A1–A3 + A4-A5 + C1-C4 + D)”.
Modules A1-A3 cover material procurement processes (raw and auxiliary materials) as well as production processes.
Module A4 considers the distribution of the finished product to the installation site in Norway. The barriers are first transported by road from the zinc-coating shop to the Port of Genoa, covering a distance of approximately 290 km. At the port, the products are loaded onto a ship and transported by sea to a Norwegian port over a distance of approximately 5500 km. Once in Norway, the barriers complete their journey with approximately 40 km road transport by truck before being delivered to the customer.
Module A5 considers the installation of the finished product at the place of delivery. For the assembly of the barriers, the use of the diesel pile driver for driving the poles into the ground is considered.
Modules C1-C4 consider the uninstallation, transport, sorting and disposal of components deriving from the end-of-life operations of road barriers. These operations are not directly controllable by the company: in this regard, literature data relating to the construction sector are therefore used:

- an average diesel consumption equivalent to 46 MJ for each ton of material demolished;
- an average distance of 300 km to transport the material to the recovery center;
- an average electricity consumption of 28 kWh for each ton of material sorted.

Furthermore, a percentage equal to 11,2% of the steel is considered not destined for recovery operations but is sent to landfill.
Module D considers the potential for recovery and recycling of steel from end-of-life processes: the calculation of the environmental benefits of steel recovery is based on the guidelines provided in the document “Product Category Rules for Type III environmental product declaration of construction products to EN 15804:2012 – Par. 6.3.4.6. Benefits and loads beyond the product system boundary, information Module D”.

DESCRIPTION OF MAIN ACTIVITIES

Marcegaglia is the first global manufacturer of steel road safety barriers. Starting from the semi-finished steel products of guaranteed quality, hot-dip galvanized, road barriers are projected, certified by experimental tests and developed in compliance with the specific regulations of the reference markets. The production cycle begins with the arrival of the raw materials in the company by road. The raw materials consist of coils, strips and sheets arriving mainly from the other companies of the Marcegaglia group. After arriving at the factory, the raw materials are processed by the respective plants to obtain the various components that make up the road safety barrier or its accessory component. The materials are partly delivered to the poles and bands profiling lines and partly to the presses to produce auxiliary parts (some components are sent directly to the storage areas). At the end of this part of the production cycle, all the elements that make up the road safety barrier destined for storage are obtained.

PRODUCTION OF PROFILES FOR POSTS AND CURRENT:

The profiles are produced on profiling lines complete with an automatic unloading section. The initial section consists of the unwinder on which the strips are loaded, to be unrolled and feed the line itself. Downstream of the loading area there is a bench for leveling which, by pressing on the incoming strips metal, eliminates any bends or undulations present. This is followed by the butting area and the actual welding. The semi-finished product then passes to the punching machine where the holes and slots that will be used in the assembly phase of the guardrail are made. The transfer from the punching area to the profile forming area takes place by means of a roller path. The profiling takes place by passing the metal strip through the forming rollers which create the open profile of different shapes and sizes. To avoid excessive overheating due to friction of the material during processing, a cooling emulsion is used. Once the desired shape and size of the section has been obtained, the profile is cut to size in a special guillotine shear. The cut profile then reaches the roller path which transports it to the automatic unloading and packing area. This last operation consists in the manual strapping of the bundles of profiles. The packs are then placed in the finished product storage area by forklift.

WAVES PRODUCTION:

The activity consists in the production of guardrail waves beam starting from the strips that are transported to the entrance to the profiling line.




SPACER PRODUCTION:

There is a line to produce a particular element of road safety barriers called spacer. The raw material used is essentially constituted by steel strips of the required width. The initial section consists of the decoiler, or the rotating support on which the strips are loaded, to be unrolled and feed the line itself. The machine unwinds the strip, which is subsequently stretched through a compact roller nerveer. A battery of hydraulically operated molds carries out all the drilling according to drawing. Subsequently, a second station carries out the first shaping with subsequent wrapping of the remaining sheet around a core. Finally, automatically, the welding is carried out on the produced. The assembly of the road barrier does not take place in the company but directly at the place of use. The pieces produced are stored in the warehouse or in the external area waiting to be sent to external plants for galvanizing.

ALLOCATION RULES:

An allocation was made on a mass basis for energy consumption and waste.

SYSTEM DIAGRAM



CONTENT INFORMATION

The average weight of one unit of product, per declared unit, is 52 kg/m.

Product content	Lenght, m	Post-consumer recycled content	Biogenic material, weight-% and kg C/kg
Steel	1	73 %	0

Packaging materials	Weight, kg	Weight-% (versus the product)	Biogenic material, kg C/product or declared unit
Plastic film	0.011	0.04%	0
Plastic strapping	0.05	0.2%	0

The quantities of such packaging in relation to one ton of final product represent less than 1%.

Electricity information

The electricity used in the manufacturing process of module A3 accounts less than 30% of the GWP-GHG results of modules A1-A3 and the impact of electricity use in the manufactory phases is 0.60 kgCO2 eq/kWh. The electricity has been modelled using the information provided in the AIB report 2025, considering the residual mix of Italy.

Allocation rules

An allocation was made on a mass basis for energy consumption, water discharges, atmospheric emissions and waste.

MODULES DECLARED

Modules declared, geographical scope, share of specific data (in GWP-GHG indicator) and data variation:

	Product stage			Construction process stage		Use stage							End of life stage				Resource recovery stage
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	X	X	X	X	X	ND	ND	ND	ND	ND	ND	ND	X	X	X	X	X
Geography	GLO	GLO	IT	EU	EU	-	-	-	-	-	-	-	GLO	EU	EU	EU	EU
Specific data used	80.7%					-	-	-	-	-	-	-	-	-	-	-	-
Variation products	-					-	-	-	-	-	-	-	-	-	-	-	-
Variation sites	Not relevant					-	-	-	-	-	-	-	-	-	-	-	-

X = Module considered | **ND** = Module not declared | **GLO** = Global | **IT** = Italy | **EU** = Europe

DATA QUALITY

Data quality was assessed in accordance with EN15804+A2 and the General Programme Instructions of the International EPD System (version 5.0.1, Annex A).

Data refer to the same monitoring period and set of EPD Terminal for safety barriers by Marcegaglia Buildtech S.r.l. already publish on EPD International and the data quality requirements are considered to be fulfilled. The products included were designed to be launched on the market in the coming year.

Data have been collected by direct interviews with employers involved in production processes, during specific field-visits in different plant sections or derived from registered company reports. Collected data refer to the monitoring period 2025 calendar year, considered as representative period for all production processes. Secondary representative data refer to the Ecoinvent database v.3.11.

The EPD is based on data collected by Marcegaglia over a one-year period (2025). It is a representation of the production of Terminal for safety barriers.

The EPD incorporates both primary data collected directly from the company and secondary data come from Ecoinvent database. The quality of the data assessed in terms of temporal coverage, geographical, and technological representativeness is rated as very good.

Life cycle stage	Data contribution to GWP [%]	Geographical representativeness	Temporal representativeness	Technological representativeness
A1 Production of steel	77.8%	Very good	Very good	Very good

Process	Source type	Source	Reference year	Data category	Share of primary data, of GWP-GHG results for A1-A3
Manufacturing of product	Collected data	EPD owner	2025	Primary data	0.9%
Generation of electricity used in manufacturing of product	European Residual Mixes 2024 Association of Issuing Bodies	AIB Version 1.0, 2025-05-30	2024	Primary data	1.3%
Transport of steel to manufacturing site	Database	Ecoinvent v3.11	2007/2015	Primary data	5.6%
Production of steel	EPD Database	EPD Ecoinvent v3.11	2025	Primary data, secondary data	72.9%
Production of packaging	Database Collected data	Ecoinvent v3.11 EPD owner	2018	Primary data, secondary data	0%
Total share of primary data, of GWP-GHG results for A1-A3					80.7%

ENVIRONMENTAL INFORMATION

The environmental performance indicators refer to 1 linear m of road barrier.

The characterization factors used in this assessment are based on EN 15804+A2 - EF 3.1, which provide a method for quantifying the environmental impact.

Environmental impact

Impact category	Abb.	Unit
Climate change - total	GWP - t	kg CO_2 eq
Climate change - Fossil	GWP - fossil	kg CO_2 eq
Climate change - Biogenic	GWP - biogenic	kg CO_2 eq
Climate change - Land use and LU change	GWP - luluc	kg CO_2 eq
Climate change - Greenhouse Gases	GWP - GHG	kg CO_2 eq.
Ozone depletion	ODP	kg CFC11 eq
Photochemical ozone formation	POCP	kg NMVOC eq
Acidification of land and water	AP	mol H+ eq
Eutrophication	EP - freshwater	kg P eq
	EP - marine	kg N eq
	EP - terrestrial	mol N eq
Water use *	WDP	m^3 depriv.
Resource use, fossils *	ADP - F	MJ
Resource use, minerals, and metals *	ADP - MM	kg Sb eq

** The results of this environmental impact indicator shall be used with care as the uncertainties of the results are high and as there is limited experience with the indicator.*

Resource use

Impact category	Abb.	Unit
Use of renewable primary energy excluding renewable primary energy resources used as raw materials	PERE	MJ
Use of renewable primary energy resources used as raw materials	PERM	MJ
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	PERT	MJ
Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials	PENRE	MJ
Use of non-renewable primary energy resources used as raw materials	PENRM	MJ
Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials)	PENRT	MJ
Use of secondary material	SM	kg
Use of renewable secondary fuels	RSF	MJ
Use of non-renewable secondary fuels	NRSF	MJ
Use of net fresh water	FW	m^3

Waste production

Impact category	Abb.	Unit
Hazardous waste disposed	HW	kg
Non-hazardous waste disposed	NHW	kg
Radioactive waste disposed	RW	kg

Output flows

Impact category	Abb.	Unit
Reuse	REUSE	kg
Materials for recycling	RECYCLE	kg
Materials for energy recovery	EN-REC	kg
Exported energy-electricity	EE-E	MJ
Exported energy-thermal energy	EE-T	MJ

TERMINAL FOR SAFETY BARRIERS

Abb.	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP - t	kg CO_2 eq	1.13E+02	6.21E+00	1.51E+00	2.40E-01	1.64E+00	4.94E-01	3.64E-02	-3.47E+01
GWP - fossil	kg CO_2 eq	1.09E+02	6.20E+00	1.50E+00	2.40E-01	1.64E+00	4.76E-01	3.64E-02	-3.46E+01
GWP - biogenic	kg CO_2 eq	4.47E+00	1.70E-03	3.02E-04	4.82E-05	9.68E-04	1.63E-02	1.75E-05	-5.60E-02
GWP - luluc	kg CO_2 eq	5.94E-02	2.66E-03	1.54E-04	2.46E-05	5.91E-04	1.42E-03	2.08E-05	-2.21E-02
GWP - GHG	kg CO_2 eq	1.12E+02	6.21E+00	1.51E+00	2.40E-01	1.64E+00	4.78E-01	3.64E-02	-3.47E+01
ODP	kg CFC-11 eq	5.87E-07	1.13E-07	2.23E-08	3.57E-09	3.59E-08	7.96E-09	1.01E-09	-1.67E-07
POCP	kg NMVOC eq	3.64E-01	8.02E-02	2.05E-02	3.28E-03	8.61E-03	1.15E-03	3.86E-04	-1.16E-01
AP	mol H+ eq	5.57E-01	9.61E-02	1.34E-02	2.15E-03	5.43E-03	2.37E-03	2.55E-04	-1.49E-01
EP - freshwater	kg P eq	2.64E-02	3.28E-04	4.84E-05	7.73E-06	1.16E-04	4.39E-04	3.18E-06	-2.04E-02
EP - marine	kg N eq	1.21E-01	2.49E-02	6.26E-03	1.00E-03	1.85E-03	4.18E-04	9.78E-05	-3.38E-02
EP - terrestrial	mol N eq	1.20E+00	2.75E-01	6.85E-02	1.09E-02	2.01E-02	3.58E-03	1.07E-03	-3.46E-01
WDP	m^3 depriv.	2.20E+01	3.42E-01	5.68E-02	9.07E-03	1.36E-01	2.54E-01	3.96E-02	-1.07E+01
ADP - F	MJ	1.19E+03	8.23E+01	1.96E+01	3.13E+00	2.40E+01	1.11E+01	8.91E-01	-3.66E+02
ADP - MM	kg Sb eq	7.73E-04	1.40E-05	5.25E-07	8.38E-08	4.61E-06	1.03E-06	5.30E-08	-2.55E-04
PERE	MJ	2.85E+01	1.03E+00	1.23E-01	1.96E-02	3.71E-01	2.52E+00	8.33E-03	-3.65E+01
PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	2.85E+01	1.03E+00	1.23E-01	1.96E-02	3.71E-01	2.52E+00	8.33E-03	-3.65E+01
PENRE	MJ	1.19E+03	8.23E+01	1.96E+01	3.13E+00	2.40E+01	1.11E+01	8.91E-01	-3.66E+02
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	1.19E+03	8.23E+01	1.96E+01	3.13E+00	2.40E+01	1.11E+01	8.91E-01	-3.66E+02
SM	kg	3.74E+00	3.78E-02	8.11E-03	1.30E-03	1.01E-02	1.15E-03	2.22E-04	-6.24E+00
RSF	MJ	1.49E-02	3.11E-04	2.12E-05	3.39E-06	1.34E-04	4.90E-06	4.63E-06	-3.81E-03
NRSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m^3	5.05E-01	8.43E-03	1.38E-03	2.21E-04	3.35E-03	6.90E-03	9.25E-04	-2.75E-01
HW	kg	3.62E+00	1.14E-01	2.20E-02	3.51E-03	3.50E-02	2.41E-02	1.01E-03	-1.38E+01
NHW	kg	1.54E+02	2.13E+00	3.20E-01	5.11E-02	7.15E-01	2.16E+00	2.34E-02	-1.86E+02
RW	kg	3.96E-04	1.75E-05	2.05E-06	3.27E-07	6.61E-06	8.10E-05	1.30E-07	-2.72E-04
REUSE	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RECYCLE	kg	3.46E-02	3.37E-02	8.72E-05	1.39E-05	2.90E-04	1.13E-03	9.65E-06	-1.80E-02
EN-REC	kg	1.21E-04	3.64E-06	2.78E-07	4.45E-08	1.06E-06	9.55E-08	1.72E-08	-1.43E-04
EE-E	MJ	2.59E-01	1.08E-02	9.27E-04	1.48E-04	4.05E-03	5.47E-02	5.78E-05	-9.93E-02
EE-T	MJ	2.47E+00	1.23E-02	4.34E-04	6.93E-05	4.31E-03	6.21E-04	3.07E-05	-1.88E-01

- Additional impact results for 100% Landfill end-of-life scenarios:

Abb.	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP - t	kg CO_2 eq	1.13E+02	6.21E+00	1.51E+00	2.40E-01	1.64E+00	4.94E-01	3.25E-01	0.00E+00
GWP - fossil	kg CO_2 eq	1.09E+02	6.20E+00	1.50E+00	2.40E-01	1.64E+00	4.76E-01	3.25E-01	0.00E+00
GWP - biogenic	kg CO_2 eq	4.47E+00	1.70E-03	3.02E-04	4.82E-05	9.68E-04	1.63E-02	1.56E-04	0.00E+00
GWP - luluc	kg CO_2 eq	5.94E-02	2.66E-03	1.54E-04	2.46E-05	5.91E-04	1.42E-03	1.86E-04	0.00E+00
GWP - GHG	kg CO_2 eq	1.12E+02	6.21E+00	1.51E+00	2.40E-01	1.64E+00	4.78E-01	3.25E-01	0.00E+00
ODP	kg CFC-11 eq	5.87E-07	1.13E-07	2.23E-08	3.57E-09	3.59E-08	7.96E-09	9.05E-09	0.00E+00
POCP	kg NMVOC eq	3.64E-01	8.02E-02	2.05E-02	3.28E-03	8.61E-03	1.15E-03	3.44E-03	0.00E+00
AP	mol H+ eq	5.57E-01	9.61E-02	1.34E-02	2.15E-03	5.43E-03	2.37E-03	2.28E-03	0.00E+00
EP - freshwater	kg P eq	2.64E-02	3.28E-04	4.84E-05	7.73E-06	1.16E-04	4.39E-04	2.84E-05	0.00E+00
EP - marine	kg N eq	1.21E-01	2.49E-02	6.26E-03	1.00E-03	1.85E-03	4.18E-04	8.73E-04	0.00E+00
EP - terrestrial	mol N eq	1.20E+00	2.75E-01	6.85E-02	1.09E-02	2.01E-02	3.58E-03	9.54E-03	0.00E+00
WDP	m^3 depriv.	2.20E+01	3.42E-01	5.68E-02	9.07E-03	1.36E-01	2.54E-01	3.53E-01	0.00E+00
ADP - F	MJ	1.19E+03	8.23E+01	1.96E+01	3.13E+00	2.40E+01	1.11E+01	7.96E+00	0.00E+00
ADP - MM	kg Sb eq	7.73E-04	1.40E-05	5.25E-07	8.38E-08	4.61E-06	1.03E-06	4.73E-07	0.00E+00

- Additional impact results for 100% Recycling end-of-life scenarios:

Abb.	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP - t	kg CO_2 eq	1.13E+02	6.21E+00	1.51E+00	2.40E-01	1.64E+00	4.94E-01	0.00E+00	-3.91E+01
GWP - fossil	kg CO_2 eq	1.09E+02	6.20E+00	1.50E+00	2.40E-01	1.64E+00	4.76E-01	0.00E+00	-3.90E+01
GWP - biogenic	kg CO_2 eq	4.47E+00	1.70E-03	3.02E-04	4.82E-05	9.68E-04	1.63E-02	0.00E+00	-6.30E-02
GWP - luluc	kg CO_2 eq	5.94E-02	2.66E-03	1.54E-04	2.46E-05	5.91E-04	1.42E-03	0.00E+00	-2.49E-02
GWP - GHG	kg CO_2 eq	1.12E+02	6.21E+00	1.51E+00	2.40E-01	1.64E+00	4.78E-01	0.00E+00	-3.90E+01
ODP	kg CFC-11 eq	5.87E-07	1.13E-07	2.23E-08	3.57E-09	3.59E-08	7.96E-09	0.00E+00	-1.88E-07
POCP	kg NMVOC eq	3.64E-01	8.02E-02	2.05E-02	3.28E-03	8.61E-03	1.15E-03	0.00E+00	-1.31E-01
AP	mol H+ eq	5.57E-01	9.61E-02	1.34E-02	2.15E-03	5.43E-03	2.37E-03	0.00E+00	-1.68E-01
EP - freshwater	kg P eq	2.64E-02	3.28E-04	4.84E-05	7.73E-06	1.16E-04	4.39E-04	0.00E+00	-2.30E-02
EP - marine	kg N eq	1.21E-01	2.49E-02	6.26E-03	1.00E-03	1.85E-03	4.18E-04	0.00E+00	-3.80E-02
EP - terrestrial	mol N eq	1.20E+00	2.75E-01	6.85E-02	1.09E-02	2.01E-02	3.58E-03	0.00E+00	-3.90E-01
WDP	m^3 depriv.	2.20E+01	3.42E-01	5.68E-02	9.07E-03	1.36E-01	2.54E-01	0.00E+00	-1.21E+01
ADP - F	MJ	1.19E+03	8.23E+01	1.96E+01	3.13E+00	2.40E+01	1.11E+01	0.00E+00	-4.13E+02
ADP - MM	kg Sb eq	7.73E-04	1.40E-05	5.25E-07	8.38E-08	4.61E-06	1.03E-06	0.00E+00	-2.87E-04

ADDITIONAL ENVIRONMENTAL INFORMATION

The steel used has an average recycled content of 73%: this percentage is calculated as a weighted average of the incoming raw material. The steel supplies come from blast furnace (with an average recycled content of 16.6%) or from an electric arc furnace (with an average recycled content of 81.5%).

Regardless of the type of product considered, the element that most affects the final result is the purchased steel. It should be noted that at the end of its useful life, once the road barrier has been disassembled it is destined for recycling. The 88.8% of the steel recovered is intended for recycling, the value is consistent with the report released by ISPRA in 2025: “Rapporto rifiuti speciali” di ISPRA – n° 416/2025.

The products do not contain hazardous substances from the SVHC Candidate List for Authorization in quantities greater than 0.1%.

VERSION HISTORY

Original version of the EPD, 2026-07-20.

ABBREVIATIONS

Abbreviation	Definition
EN	European Norm (Standard)
GPI	General Programme Instructions
ISO	International Organization for Standardization
CEN	European Committee for Standardization
CPC	Central product classification
SVHC	Substances of Very High Concern
ND	Not Declared
D	Declared

REFERENCES

- General Programme Instructions of the International EPD® System. Version 5.0.1;
- PCR 2019:14 Construction products (EN 15804+A2) vers. 2.0.1 (2025-06-05) ;
- c-PCR-010 (PCR 2019:14) Guardrails and bridge parapets, 2019:14, version 1.0.1, CPC 532;
- Product Category Rules for Type III environmental product declaration of construction products to EN 15804:2012;
- Ecoinvent database v.3.11 – April, 2025;
- ISO 14025: 2010 “Environmental labels and declarations - Type III environmental declarations - Principles and procedures”;
- ISO 14040:2021 “Environmental management - Life cycle assessment - Principles and framework”;
- ISO 14044:2021 “Environmental management - Life cycle assessment - Requirements and guidelines”;
- ISO 15804:2021 “Sustainability of buildings - Environmental product declarations - Development framework rules by product category”;
- European Residual Mixes 2024 Association of Issuing Bodies “European Residual Mixes Results of the calculation of Residual Mixes for the calendar year 2024” – 2025-05-30;
- Environmental engineering "WASTE FROM CONSTRUCTION AND LCA DEMOLITION FROM THE DEMOLITION OF 51 RESIDENTIAL BUILDINGS" - Michele Paleari, Politecnico di Milano – 26-11-2015;
- ISPRA in 2025: “Rapporto rifiuti speciali” di ISPRA – n° 416/2025;
- Internal LCA Study “Not Yet On the Market_Barriers_Rev1” – May 2026.



MARCEGAGLIA

Registered seat:
Via Bresciani, 16 - 46040
Gazoldo degli Ippoliti (MN) – Italy

Main offices and plants:
Roveri street, 4 – 15068
Pozzolo Formigaro (AL) – Italy

Phone +39 0371 20681
cantieristica@marcegaglia.com
www.marcegagliabuildtech.com

ECO PLATFORM
EPD
VERIFIED

EPD
INTERNATIONAL EPD SYSTEM